DUCHESNE COUNTY MONUMENT SURVEY RECORD T4S SEC 13 | SEC 18 5/8" REBAR AT BASE SEC 24 | SEC 19 STATION CONTROL POINT R8W R7W U.S.B.&M. N - 2513 ½" REBAR WITH GREEN CAP S 89°33'11" W SECTION CORNER S 89°18'48" W <u>2607.22</u>' 51.64 NORTH FOUND GAL PIPE AND CAP AT 1/4 CORNER / ½" REBAR WITH GREEN CAP NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40'09'16.01931"N AND LONG. 110'45'51.61780"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER SCALE: 1"=30' *30'*

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND AN ALUMINUM BLM PIPE AND CAP MONUMENT AT POSITION OF SECTION CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET TWO ½" REBAR WITH GREEN PLASTIC CAPS MARKED "REFERENCE MARKER" AS REFERENCE POINTS AS SHOWN



MARKING ON MONUMENT

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7215443.649 E: 1856654.959 NAVD88 EL: 6016.98'

LATITUDE: 40°07'32.50205" N
LONGITUDE: 110°43'36.01962" W

ELLIPSOID HEIGHT: 5963.28'

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300040S0080W0_100400



PHOTO OF CORNER FACING SOUTH

CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>20 MAY '19</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

